



# Sun Control Window Films


## Performance Results:

Visible Light Transmitted	37%
Total Solar Energy Rejected	56%
UV Light Rejected	99%
Glare Reduction	58%
Visible Light Reflected	20%
Solar Heat Reduction	45%



## Neutral 35

*A higher standard*



RE35NEARL



### Neutral 35 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Comprehensive 3M manufacturer's warranty
- Reduces glare and eye discomfort
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	37%	22%	33%	19%
Total Solar Energy Rejected	56%	61%	50%	63%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	58%	56%	58%	58%
Visible Light Reflected	20%	9%	24%	10%
Shading Coefficient	0.51	0.45	0.58	0.43
Emissivity	0.84	0.84	0.84	0.84
U Value	1.06	1.06	0.50	0.50
Solar Heat Reduction	45%	35%	28%	22%



The Skin Cancer Foundation recommends this 3M Window Film product as an effective UV protectant.

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.

### 3M Building and Commercial Services Division

3M Center, Building 223-2S-24  
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2007 70-0709-0170-0 (371.5)ii